

ONTARIO EXPRESS ORDER FORM

NEOX Tilt-In-Space

**CANADIAN MSRP
PRICE ONLY**



SEND

Version 01

Effective April 7, 2020

NEOX™



Date:	P.O.#:
Client Last Name:	Client First Name:
Ordered by:	
Establishment:	
Address:	
Phone:	Fax:
Email address:	

STANDARD FEATURES	
Color: Silver	Footplates: Aluminium Flip-Up
Seat Width: 16", 18", 20"	Brakes: Push to lock
Seat Depth: 16", 18"	Axles: Threaded Axles
Seat-to-Floor Height: 13" to 19"	Handrim: Aluminium
Seat Type: Rigid Seat Pan	Rear Wheels: 20", 22", 24"
Back Height: 22"	Front Wheel: 5", 6", 8"
Back Angle: 95°	Tilt: -5° to 45°
Armrest: T Type/Full length Armpad, adj. from 7" to 12"	Anti-tip
Footrest: 70° Footrest Swing Away	Stroller Bar

Order confirmation by email	Yes ☐	No ☐
Subscribe to Physipro newsletter	Yes ☐	No ☐

	Price Specification	...	Code to be completed by the customer service agent
	Technical Specification		

ADP DEVICE CODE:
WM0001255

MODEL										
	DYNAMIC TILT: See configuration chart according to tilt angle.									
PRODUCT	DESCRIPTION							CODE	PRICE	CHOICE
4 Wheels Neox	Tilt-in-space - 45° 							NX1EXPEA	\$2917	☐
6 Wheels Neox	Tilt-in-space - 45° 							NX2EXPEA	\$3700	☐
SEAT-TO-FLOOR HEIGHT										
Seat-to-Floor Height	13" ☐	14" ☐	15" ☐	16" ☐	17" ☐	18" ☐	19" ☐	-	N/C	←
SEAT WIDTH										
Standard Frame <i>(WAMA)</i>	16" ☐			18" ☐			20 " ☐	NX...	N/C	←
SEAT DEPTH										
Standard Frame	16" ☐			18" ☐				NX...	N/C	←
SEAT TYPE										
Seat type	Aluminium Rigid Seat Pan							NX5	STD	☐
FOOTREST										
70° Swing Away	Adjustable from 14" to 19" Desired Length: _____ "							NX70	STD	←
FOOTPLATE										
Flip-Up Footplate	8" depth only available							NX...	N/C	☐
Oversized - Angle and Depth Adjustable <i>(WAMJ)</i>	9" depth only available							NX...X...	\$195 Pair	☐
Heel Support Strap	Adjustable in length							NX28	N/C	☐
WHEEL LOCKS										
Wheel Locks	Fixed Extension Handle - 6"							NX30E	N/C	☐
ELEVATING AND ARTICULATING LEGREST										
Elevating and Articulating Legrest <i>(WAMK)</i>	Adjustable in Height from 14" to 16"							NX15	\$545 Pair	☐
	Adjustable in Height from 17" to 19"							NX16	\$545 Pair	☐

ONTARIO EXPRESS ORDER FORM

NEOX Tilt-In-Space

**CANADIAN MSRP
PRICE ONLY**

Version 01
Effective April 7, 2020

CASTERS WHEELS (POLYURETHANE)								
PRODUCT	DESCRIPTION				CODE	PRICE	CHOICE	
Casters Wheels	5" x 1 ½" ☐		6" x 1 ½" ☐		8" x ½" ☐	WHUN...	N/C	←
REAR WHEEL SIZE								
Wheels	20" ☐		22" ☐		24" ☐	-	N/C	←
RIMS								
Rims	Mag Wheel					NX52MA	N/C	☐
	Spoke Wheel					NX52SW	N/C	☐
REAR WHEEL TIRE								
Tire	Polyurethane					-	N/C	☐
HANDRIM OPTIONS								
Handrim	Aluminium					NX44	STD	☐
	Plastic Coated (WAMO)					NX45	\$130 Pair	☐
AXLES TYPE								
Axles Type	Threaded Axles					NX47	STD	☐
	Quick Release Axles (WAMU)					NX48E	\$92 Pair	☐
ANTI-TIP								
Anti-Tip	Not available with 6 wheels configuration					NX40	STD	☐
POSITIONING STRAP								
Positioning Strap	Auto style positioning strap, 2"					NX41	\$35	☐
TRANSIT OPTION								
Transit Option	Four Distinct Tie-Down Securement Locations					NX42	\$95	☐
BACKREST, HEADREST & CUSHION								
Headrest	Symbio Headrest Support with Small (7" x 4") Standard Pad					NX33-KS	\$665	☐
	Symbio Headrest Support with Medium (8" x 5") Standard Pad					NX33-KM		☐
	Symbio Headrest Support with Large (9" x 6") Standard Pad					NX33-KL		☐
Contour Cinch Back	16" x 18" ☐	16" x 20" ☐	18" x 18" ☐	18" x 20" ☐		CINCH...	\$888	←
	20" x 18" ☐	20" x 20" ☐			←			
HP2 Contour Back (SE0001071)	16" x 18" ☐	16" x 20" ☐	18" x 18" ☐	18" x 20" ☐		HPC...	\$822	←
	20" x 18" ☐	20" x 20" ☐			←			
HP2 Profiled Back (SE0001071)	16" x 18" ☐	16" x 20" ☐	18" x 18" ☐	18" x 20" ☐		HPP...	\$822	←
	20" x 18" ☐	20" x 20" ☐			←			
Brio Cushion	16" x 16" ☐	16" x 18" ☐	18" x 16" ☐	18" x 18" ☐		NXBR-...	\$419	←
	20" x 16" ☐	20" x 18" ☐			←			
Incontinence Cover	Cinch					PD50715	\$90	☐
	Brio Cushion					S2953	\$90	☐

SPECIFICATION CHARTS

Standard 6 wheels NEOX

CANADIAN MSRP
PRICE ONLY




Version 01
Effective April 7, 2020

STANDARD 6 WHEELS NEOX - DETERMINE THE TILT ANGLE

STEP 1: Define the frame format according to the seat depth

		FRAME	
		SMALL	LARGE
SEATH DEPTH	14"	Small	NA
	15"		
	16"		
	17"		
	18"		
	19"	NA	Large
	20"		
	21"		
	22"		

STEP 2: Define the position of the tilt system according to the seat-to-floor height and the wheels diameter

		WHEELS					
		20"		22"	24"		
SEAT-TO-FLOOR HEIGHT	13"	6	NA	NA	NA	POSITION OF THE TILT SYSTEM	
	14"	NA	6	6			
	15"		5	5	6		
	16"		4	4	5		
	17"		3	3	4		
	18"		2	2	3		
	19"		1	1	2		
	20"	NA	NA	1			
		D5"	D6"				
		CASTERS					

 **NOTE :** D5"/D6" = "D" means the use of a dynamic fork.

STEP 3: Define the tilt angle according to the frame format (STEP 1), the position of the tilt system (STEP 2) and the type of armrest

		FRAME		ARMTREST
		SMALL	LARGE	
POSITION OF THE TILT SYSTEM	6	30°	26°	
	5	36°	32°	
	4	43°	39°	
	3	45°	45°	
	2	45°	45°	
	1	45°	45°	
		TILT ANGLE (+/- 1°)		

NOTE : The power tilt, the foot operated brakes, the dynamic backrest and the oxygen tank holder can influence the results

SPECIFICATION CHARTS

Standard 4 wheels NEOX


STANDARD 4 WHEELS NEOX - DETERMINE THE TILT ANGLE

STEP 1: Define the frame format according to the seat depth.

		FRAME	
		SMALL	LARGE
SEATH DEPTH	14"	Small	NA
	15"		
	16"		
	17"		
	18"		
	19"	NA	Large
	20"		
	21"		
	22"		

STEP 2: Define the position of the tilt system according to the seat-to-floor height and the wheels diameter

		WHEELS													
		12"			20"				22"			24"			
SEAT-TO-FLOOR HEIGHT	13"	6	6		6	6	6								
	14"	5	5		5		5	6	6	6	6	6			
	15"	4	4	6	4		4	5	5	5	5	6	6	6	
	16"	3	3	5	3		3	4	4	4	4	5	5	5	
	17"	2	2	4	2		2	3	3	3	3	4	4	4	
	18"	1	1	3	1		1	2	2	2	2	3	3	3	
	19"			2				1	1	1	1	2	2	2	
	20"			1								1	1	1	
			5"	6"	8"	5"	D5"	6" 	6"	D6"	6"	D6"	8"	D6"	8"
		CASTERS													




6
5
4
3
2
1

 **NOTE:** 6" = This caster is arranged in a low configuration.

 **NOTE:** D6" = "D" means the use of a dynamic fork.

STEP 3: Define the tilt angle according to the frame format (STEP 1), the position of the tilt system (STEP 2) and the type of armrest

		FRAME		ARMREST
		SMALL	LARGE	
		T	T	
	POSITION OF THE TILT SYSTEM	6	21°	20°
		5	26°	26°
		4	32°	30°
		3	38°	36°
		2	45°	43°
		1	45°	45°
		TILT ANGLE (+/- 1°)		

STEP 4: To guarantee a minimum stability of 10° in the least stable configuration, validate the maximum tilt angle according to the angle of the backrest and the weight of the user

BACKREST ANGLE	75 KG (165 LB)	115 KG (250 LB)	160 KG (350 LB)
	MAX TILT ANGLE	MAX TILT ANGLE	MAX TILT ANGLE
90°	46°	46°	22°
95°	46°	46°	22°
100°	46°	45°	22°
105°	46°	43°	22°
110°	46°	40°	22°
115°	46°	40°	22°

SPECIFICATION CHARTS

ADP Device Code

STANDARD NEOX OVERALL WIDTH
Seath width + 9 ¾" (Spoke Wheel)
Seath width + 11" (Mag Wheel)

NEOX - SEAT-TO-FLOOR HEIGHT

4 WHEELS NEOX		
WHEELS	CASTERS	SEAT-TO-FLOOR HEIGHT
20"	S5"	13" to 18"
	S6"	13" to 18"
	S6"	14" to 19"
22"	S6"	14" to 19"
	S8"	15" to 20"
24"	S8"	15" to 20"

6 WHEELS NEOX		
WHEELS	CASTERS	SEAT-TO-FLOOR HEIGHT
20"	D5"	13" to 18"
22"	D6"	14" to 19"
24"	D6"	15" to 20"
DEFINITION		
S6"	Standard Fork	
D5"-D6"	Dynamic Fork	

ADP LIST CODE

DEVICE TYPE	DEVICE CODE
Elevating Legrests (pair)	WAMK
MW - Angle Adjustable Footplates (pair)	WAMJ
MW - Seat Width Required is Greater Than 18"	WAMA
Plastic Coated Handrims	WAMO
Quick Release Axles (pair)	WAMU